

## SPECIFICATIONS

MODEL		NC 500	NC 600	NC 700	NC 800	NC 1000
DESCRIPTION						
TABLE SIZE		245X508mm	300X600mm	305X712mm	406X813mm	406X1020mm
LONGITUDINAL MOVEMENT SPEED		0.5~25M/min				
CROSS TRANSVERSE TRAVEL	MIN. SETTING UNIT	0.001mm				
	MPG	Per graduation: 0.001mmX1, 0.001mmX10, 0.001mmX100				
	RAPID SPEED	10000mm/min				
WHEELHEAD VERTICAL INFED	MIN. SETTING UNIT	0.0001mm				
	MPG	Per graduation: 0.001mmX1, 0.001mmX10, 0.001mmX100				
	RAPID SPEED	750mm/min				
SPINDLE DRIVE	POWER RATING	2.2KW(3HP)	3.7KW(5HP)	Standard 3.7KW(5HP) Optional 5.55KW(7 1/2HP), 7.4KW(10HP)		
	SPEED	50HZ2850R.P.M. 60HZ3450R.P.M.	50HZ 1450 R.P.M. 60HZ 1750 R.P.M.			
STANDARD GRINDING WHEEL	DIAMETER	∅203mm	∅304mm	∅355mm		
	WIDTH	Standard19mm Max. 25mm	32mm	50mm		
	BORE	∅31.75mm	∅76.2mm	∅127mm		
HYDRAULIC MOTOR		2.0HP			3.0HP	
FLOOR SPACE		2400X1650X1850mm	2700X1800X1950mm	2950X2150X2150mm	3290X2400X2150mm	4020X2400X2150mm

The manufacturer reserves the right to modify the design, specifications, mechanisms, etc., to improve the performances of the machine without notice. All the specifications shown above are just for reference.

# EQUIPTOP®

EQUIPTOP HITECH CORP.



CE ISO-9002



<http://www.equiptop.com.tw>

## NC PRECISION PROFILE GRINDERS

**EQUIPTOP HITECH CORP.**

NO. 500, SAN FENG RD., HOULI HSIANG, TAICHUNG, TAIWAN, R.O.C.

TEL : +886-4-25576060 (Rep.) FAX : +886-4-25569677 ; 25575866

Internet : [www.equiptop.com.tw](http://www.equiptop.com.tw) E-mail : [equiptop@ms18.hinet.net](mailto:equiptop@ms18.hinet.net)





